

別表 第4

土地改良事業等ダム工事用仮設備機械等損料算定表

40 コンクリート生産設備

分類コード	規 格			(1) 基礎価格 (千円)	(2) 標準使用 年数 (年)	標準使用			(6) 整備修 理費率 (%)	(7) 年間管 理費率 (%)	残 存 率 (%)	運転1時間当たり		供用1日当たり		換算値				摘 要
	諸 元	機関出力 (kW)	機械 質量 (t)			(3) 運転 時間 (時間)	(4) 運転 日数 (日)	(5) 供用 日数 (日)				(8) 損料率 (×10-7)	(9) 損 料 (円)	(10) 損料率 (×10-7)	(11) 損 料 (円)	運転1時間当たり		供用1日当たり		
				(12) 損料率 (×10-7)	(13) 損 料 (円)				(14) 損料率 (×10-7)	(15) 損 料 (円)										

40 コンクリート生産設備

4001 コンクリートプラント

018 〔傾胴型〕

	ミキサ容量	台数																		
0752-001	0.75 m ³	2 基	21	82	56,900	9.0	7,200	900	2,000	30	7.0	3	1,090	6,200	5,575	31,700	2,639	15,000	9,500	54,100
0753-001	0.75	3	29	95	64,800	9.0	7,200	900	2,000	30	7.0	3	1,090	7,060	5,575	36,100	2,639	17,100	9,500	61,600
1002-001	1.0	2	28	95	65,600	9.0	7,200	900	2,000	30	7.0	3	1,090	7,150	5,575	36,600	2,639	17,300	9,500	62,300
1502-001	1.5	2	38	122	80,800	9.5	7,600	940	2,100	30	7.0	3	1,033	8,350	5,476	44,200	2,546	20,600	9,214	74,400
1503-001	1.5	3	53	148	97,100	9.8	8,200	1,100	2,100	35	7.0	3	1,018	9,880	5,576	54,100	2,446	23,800	9,552	92,700
3002-001	3.0	2	83	214	125,000	11.2	9,500	1,300	2,400	35	7.0	3	879	11,000	5,288	66,100	2,215	27,700	8,767	110,000
3003-001	3.0	3	120	230	151,000	11.2	9,500	1,300	2,400	35	7.0	3	879	13,300	5,288	79,800	2,215	33,400	8,767	132,000

028 〔二軸強制練り型〕

	ミキサ容量	台数																		
1001-001	1.0 m ³	1 基	60	46	79,600	8.6	8,400	780	1,900	25	7.0	3	875	6,970	5,721	45,500	2,169	17,300	9,589	76,300
1002-001	1.0	2	120	65	119,000	8.6	8,400	780	1,900	25	7.0	3	875	10,400	5,721	68,100	2,169	25,800	9,589	114,000
1501-001	1.5	1	83	88	137,000	8.6	8,400	780	1,900	25	7.0	3	875	12,000	5,721	78,400	2,169	29,700	9,589	131,000
1502-001	1.5	2	157	107	176,000	9.8	10,000	950	2,100	35	7.0	3	835	14,700	5,576	98,100	2,006	35,300	9,552	168,000
2001-001	2.0	1	120	111	173,000	8.6	8,400	780	1,900	25	7.0	3	875	15,100	5,721	99,000	2,169	37,500	9,589	166,000
2002-001	2.0	2	183	134	219,000	9.8	10,000	950	2,100	35	7.0	3	835	18,300	5,576	122,000	2,006	43,900	9,552	209,000
2251-001	2.25	1	135	141	212,000	9.8	10,000	950	2,100	35	7.0	3	835	17,700	5,576	118,000	2,006	42,500	9,552	203,000
2252-001	2.25	2	228	157	254,000	11.2	11,500	1,100	2,400	35	7.0	3	726	18,400	5,288	134,000	1,830	46,500	8,767	223,000
2501-001	2.5	1	140	148	218,000	9.8	10,000	950	2,100	35	7.0	3	835	18,200	5,576	122,000	2,006	43,700	9,552	208,000
3001-001	3.0	1	147	152	225,000	9.8	10,000	950	2,100	35	7.0	3	835	18,800	5,576	125,000	2,006	45,100	9,552	215,000
3002-001	3.0	2	307	195	277,000	11.2	11,500	1,100	2,400	35	7.0	3	726	20,100	5,288	146,000	1,830	50,700	8,767	243,000
4501-001	4.5	1	162	172	295,000	9.8	10,000	950	2,100	35	7.0	3	835	24,600	5,576	164,000	2,006	59,200	9,552	282,000

受材用制御盤、監視装置、印字記録装置及び水分計を含み、コンプレッサ、ポンプ等は含まない。

41 コンクリート運搬機械

分類コード	規 格			(1)	(2)	標準使用			(6)	(7)	残存率 (%)	運転1時間当たり		供用1日当たり		換算値				摘 要	
	諸 元	機関出力 (kW)	機械 質量 (t)	基礎価格 (千円)	標準使用 年数 (年)	(3) 運転 時間 (時間)	(4) 運転 日数 (日)	(5) 供用 日数 (日)	整備修 理費率 (%)	年間管 理費率 (%)		(8) 損料率 (×10-7)	(9) 損 料 (円)	(10) 損料率 (×10-7)	(11) 損 料 (円)	運転1時間当たり		供用1日当たり			
																(12) 損料率 (×10-7)	(13) 損 料 (円)	(14) 損料率 (×10-7)	(15) 損 料 (円)		
41 コンクリート運搬設備																				移動側の塔は2基とし、その支点間距離は100mとする。 塔(固定側10m、移動側10m)、ガイドロープ、コンクリートバケットを含む。整備修理費率には、ワイヤーロープの取替費を含む。	
4101 ケーブルクレーン																					
018 〔軌索式・片側移動・サイリスタレオナード方式〕																					
定格荷重																					
0450-001	5 t	157	106	272,000	7.8	13,800	1,300	2,200	20	7.0	3	496	13,500	4,686	127,000	1,243	33,800	7,800	212,000		スパン250m
0600-001	6.5	212	128	320,000	7.8	13,800	1,300	2,200	20	7.0	3	496	15,900	4,686	150,000	1,243	39,800	7,800	250,000		スパン300m
0900-001	9.5	425	193	445,000	7.8	13,800	1,300	2,200	20	7.0	3	496	22,100	4,686	209,000	1,243	55,300	7,800	347,000		スパン400m
1350-001	13.5	870	400	687,000	7.8	13,800	1,300	2,200	20	7.0	3	496	34,100	4,686	322,000	1,243	85,400	7,800	536,000		スパン450m
028 〔両側走行式・サイリスタレオナード方式〕																					
定格荷重																					
1350-001	13.5 t	602	413	891,000	10.3	18,900	1,800	2,900	25	7.0	3	389	34,700	4,159	371,000	1,027	91,500	6,693	596,000		スパン450m
2000-001	20	1,008	520	1,080,000	10.3	18,900	1,800	2,900	25	7.0	3	389	42,000	4,159	449,000	1,027	111,000	6,693	723,000		スパン500m
038 〔弧動式・サイリスタレオナード方式〕																					
定格荷重																					
1350-001	13.5 t	514	303	675,000	10.3	18,900	1,800	2,900	25	7.0	3	389	26,300	4,159	281,000	1,027	69,300	6,693	452,000		スパン450m
2000-001	20	888	442	924,000	10.3	18,900	1,800	2,900	25	7.0	3	389	35,900	4,159	384,000	1,027	94,900	6,693	618,000	スパン500m	
048 〔固定式・サイリスタレオナード方式〕																					
定格荷重																					
0900-001	9.5 t	350	122	197,000	7.8	13,800	1,400	2,200	20	7.0	3	496	9,770	4,686	92,300	1,243	24,500	7,800	154,000	スパン400m	
1350-001	13.5	470	160	256,000	7.8	13,800	1,400	2,200	20	7.0	3	496	12,700	4,686	120,000	1,243	31,800	7,800	200,000	スパン450m	
2000-001	20	830	280	519,000	7.8	13,800	1,400	2,200	20	7.0	3	496	25,700	4,686	243,000	1,243	64,500	7,800	405,000	スパン500m	
4102 ジブクレーン																					
018 〔走行式・サイリスタレオナード方式〕																					
定格荷重																					
0900-001	9.5 t	190	185	358,000	6.7	11,100	1,300	2,100	20	7.0	3	617	22,100	4,543	163,000	1,477	52,900	7,805	279,000	コンクリートバケットを含む。整備修理費率には、ワイヤーロープの取替費を含む。	
1350-001	13.5	266	240	462,000	8.6	14,300	1,500	2,700	25	7.0	3	514	23,700	4,026	186,000	1,274	58,900	6,748	312,000		

41 コンクリート運搬機械

分類コード	規 格			(1)	(2)	標準使用			(6)	(7)	残 存 率 (%)	運転1時間当たり		供用1日当たり		換算値				摘 要		
	諸 元	機関出力 (kW)	機械 質量 (t)	基礎価格 (千円)	標準使用 年数 (年)	(3) 運転 時間 (時間)	(4) 運転 日数 (日)	(5) 供用 日数 (日)	整備修 理費率 (%)	年間管 理費率 (%)		(8) 損料率 (×10-7)	(9) 損 料 (円)	(10) 損料率 (×10-7)	(11) 損 料 (円)	運転1時間当たり		供用1日当たり				
																(12) 損料率 (×10-7)	(13) 損 料 (円)	(14) 損料率 (×10-7)	(15) 損 料 (円)			
4103 タワークレーン																					本体にはクライミング装置、コンクリートバケットを含み、中間タワーを含まない。整備修理費率には、ワイヤーロープの取替費を含む。	
018 〔油圧式・定置型〕																						
定格荷重 作業半径																						
0540-001	本体	5.0 t	40 m	83	125	175,000	10.5	13,500	1,300	2,000	20	7.0	3	507	8,870	6,100	107,000	1,411	24,700	9,525		167,000
0540-002	中間タワー	1m当たり	—	1	1,060	10.5	—	—	2,000	10	7.0	3	—	—	9,025	957	—	—	9,025	957		
0560-001	本体	5.0	60	133	195	265,000	10.5	13,500	1,300	2,000	20	7.0	3	507	13,400	6,100	162,000	1,411	37,400	9,525		252,000
0560-002	中間タワー	1m当たり	—	1.7	1,870	10.5	—	—	2,000	10	7.0	3	—	—	9,025	1,690	—	—	9,025	1,690		
0640-001	本体	6.5	40	96	150	201,000	10.5	13,500	1,300	2,000	20	7.0	3	507	10,200	6,100	123,000	1,411	28,400	9,525		191,000
0640-002	中間タワー	1m当たり	—	1.5	1,410	10.5	—	—	2,000	10	7.0	3	—	—	9,025	1,270	—	—	9,025	1,270		
0650-001	本体	6.5	50	132	250	347,000	10.5	13,500	1,300	2,000	20	7.0	3	507	17,600	6,100	212,000	1,411	49,000	9,525		331,000
0650-002	中間タワー	1m当たり	—	1.7	1,870	10.5	—	—	2,000	10	7.0	3	—	—	9,025	1,690	—	—	9,025	1,690		
0660-001	本体	6.5	60	160	276	393,000	10.5	13,500	1,300	2,000	20	7.0	3	507	19,900	6,100	240,000	1,411	55,500	9,525		374,000
0660-002	中間タワー	1m当たり	—	2	2,010	10.5	—	—	2,000	10	7.0	3	—	—	9,025	1,810	—	—	9,025	1,810		
0675-001	本体	6.5	75	175	330	475,000	10.5	13,500	1,300	2,000	20	7.0	3	507	24,100	6,100	290,000	1,411	67,000	9,525		452,000
0675-002	中間タワー	1m当たり	—	2.5	2,430	10.5	—	—	2,000	10	7.0	3	—	—	9,025	2,190	—	—	9,025	2,190		
0935-001	本体	9.5	35	119	150	201,000	10.5	13,500	1,300	2,000	20	7.0	3	507	10,200	6,100	123,000	1,411	28,400	9,525		191,000
0935-002	中間タワー	1m当たり	—	1.8	1,600	10.5	—	—	2,000	10	7.0	3	—	—	9,025	1,440	—	—	9,025	1,440		
0960-001	本体	9.5	60	180	310	420,000	10.5	13,500	1,300	2,000	20	7.0	3	507	21,300	6,100	256,000	1,411	59,300	9,525		400,000
0960-002	中間タワー	1m当たり	—	3	2,680	10.5	—	—	2,000	10	7.0	3	—	—	9,025	2,420	—	—	9,025	2,420		
0975-001	本体	9.5	75	215	349	486,000	10.5	13,500	1,300	2,000	20	7.0	3	507	24,600	6,100	296,000	1,411	68,600	9,525		463,000
0975-002	中間タワー	1m当たり	—	3	2,680	10.5	—	—	2,000	10	7.0	3	—	—	9,025	2,420	—	—	9,025	2,420		
1375-001	本体	13.5	75	297	422	555,000	11.8	15,700	1,500	2,300	25	7.0	3	468	26,000	5,700	316,000	1,303	72,300	8,896	494,000	
1375-002	中間タワー	1m当たり	—	4	2,910	11.8	—	—	2,300	15	7.0	3	—	—	8,461	2,460	—	—	8,461	2,460		
2175-001	本体	21.0	75	475	502	709,000	11.8	15,700	1,500	2,300	25	7.0	3	468	33,200	5,700	404,000	1,303	92,400	8,896	631,000	
2175-002	中間タワー	1m当たり	—	5	3,090	11.8	—	—	2,300	15	7.0	3	—	—	8,461	2,610	—	—	8,461	2,610		
4104 トランスファーカー																					給電装置は含まない。	
015 〔シュート式〕																						
バケット容量																						
0300-001		3.0 m ³	20	10	28,500	10.4	8,700	820	1,600	30	7.0	3	902	2,570	7,581	21,600	2,297	6,550	12,488	35,600		
0450-001		4.5	20	12	31,600	10.4	8,700	820	1,600	30	7.0	3	902	2,850	7,581	24,000	2,297	7,260	12,488	39,500		
0600-001		6.0	30	20	39,300	10.4	8,700	820	1,600	30	7.0	3	902	3,540	7,581	29,800	2,297	9,030	12,488	49,100		
025 〔リフトダンプ式〕																						
0001-001	各種	—	—	—	10.4	7,200	800	1,600	30	7.0	3	1,090	—	7,581	—	2,775	—	12,488	—			

42 コンクリート冷却設備																					
分類コード	規 格			(1) 基礎価格 (千円)	(2) 標準使用 年数 (年)	標準使用			(6) 整備修 理費率 (%)	(7) 年間管 理費率 (%)	残 存 率 (%)	運転1時間当たり		供用1日当たり		換算値				摘 要	
	諸 元	機関出力 (kW)	機械 質量 (t)			(3) 運転 時間 (時間)	(4) 運転 日数 (日)	(5) 供用 日数 (日)				(8) 損料率 (×10-7)	(9) 損 料 (円)	(10) 損料率 (×10-7)	(11) 損 料 (円)	運転1時間当たり		供用1日当たり			
																(12) 損料率 (×10-7)	(13) 損 料 (円)	(14) 損料率 (×10-7)	(15) 損 料 (円)		
42 コンクリート冷却設備																					ポンプ、配管を 含まない。整備修理費率には、 チューブ 清掃費を含む。 クーリングタワーを使用する場合は基礎価格に それぞれ次の金額を 加算する。 冷却能力(kW) 加算額(千円) 386 2,930 579 3,870 772 5,150 965 6,170 1,158 7,270
4201 クーリングプラント																					
018 〔ターボ式〕																					
冷却能力																					
0100-001	386 kW	(100JRT)	110	3.8	35,200	9.2	17,300	1,000	2,800	35	6.0	3	483	1,700	3,704	13,000	1,082	3,810	6,686	23,500	
0150-001	579	(150)	140	4.8	41,700	9.2	17,300	1,000	2,800	35	6.0	3	483	2,010	3,704	15,400	1,082	4,510	6,686	27,900	
0200-001	772	(200)	180	5.4	48,200	9.2	17,300	1,000	2,800	35	6.0	3	483	2,330	3,704	17,900	1,082	5,220	6,686	32,200	
0250-001	965 kW	(250JRT)	220	6.7	53,000	9.2	17,300	1,000	2,800	35	6.0	3	483	2,560	3,704	19,600	1,082	5,730	6,686	35,400	
0300-001	1,158	(300)	260	9.2	58,400	9.2	17,300	1,000	2,800	35	6.0	3	483	2,820	3,704	21,600	1,082	6,320	6,686	39,000	
028 〔スクリュース式〕																					
冷却能力																					
0030-001	116 kW	(30JRT)	50	2.0	8,290	12.1	6,600	600	2,800	30	6.0	3	1,189	986	4,325	3,590	3,024	2,510	7,129	5,910	
0060-001	232	(60)	60	2.4	15,000	12.1	6,600	600	2,800	30	6.0	3	1,189	1,780	4,325	6,490	3,024	4,540	7,129	10,700	
0090-001	347	(90)	70	2.8	22,000	12.1	6,600	600	2,800	30	6.0	3	1,189	2,620	4,325	9,520	3,024	6,650	7,129	15,700	

43 骨材生産設備

分類コード	規 格			(1)	(2)	標準使用			(6)	(7)	残 存 率 (%)	運転1時間当たり		供用1日当たり		換算値				摘 要
	諸 元	機関出力 (kW)	機械 質量 (t)	基礎価格 (千円)	標準使用 年数 (年)	(3)	(4)	(5)	整備修 理費率 (%)	年間管 理費率 (%)		(8)	(9)	(10)	(11)	運転1時間当たり		供用1日当たり		
						運 転 時間 (時間)	運 転 日数 (日)	供用 日数 (日)				損料率 (×10-7)	損 料 (円)	損料率 (×10-7)	損 料 (円)	(12) 損料率 (×10-7)	(13) 損 料 (円)	(14) 損料率 (×10-7)	(15) 損 料 (円)	
4302 コーンクラッシャ																				油圧ユニット、配管材を含む。シュート、ホッパは別途に一現場償却として積算し、スクラップ分の残存を考慮する。
018 〔油圧式〕																				
マントル径																				
0600-001	600 mm	30	6	13,200	12.7	8,700	1,000	2,700	50	6.0	3	1,132	1,490	4,619	6,100	2,566	3,390	8,267	10,900	
0750-001	750	45	10	22,300	12.7	8,700	1,000	2,700	50	6.0	3	1,132	2,520	4,619	10,300	2,566	5,720	8,267	18,400	
0900-001	900	75	13	25,500	12.7	8,700	1,000	2,700	50	6.0	3	1,132	2,890	4,619	11,800	2,566	6,540	8,267	21,100	
1000-001	1,000	110	16	27,900	12.7	8,700	1,000	2,700	50	6.0	3	1,132	3,160	4,619	12,900	2,566	7,160	8,267	23,100	
1200-001	1,200	110	23	39,500	12.7	8,700	1,000	2,700	50	6.0	3	1,132	4,470	4,619	18,200	2,566	10,100	8,267	32,700	
1300-001	1,300	130	29	43,400	13.8	9,600	1,400	3,100	50	6.0	3	1,026	4,450	4,235	18,400	2,394	10,400	7,413	32,200	
1500-001	1,500	190	42	55,800	13.8	9,600	1,400	3,100	50	6.0	3	1,026	5,730	4,235	23,600	2,394	13,400	7,413	41,400	
1800-001	1,800	220	68	84,700	13.8	9,600	1,400	3,100	50	6.0	3	1,026	8,690	4,235	35,900	2,394	20,300	7,413	62,800	
2100-001	2,100	300	95	119,000	13.8	9,600	1,400	3,100	50	6.0	3	1,026	12,200	4,235	50,400	2,394	28,500	7,413	88,200	
4303 ロッドミル																				ロッドは運転経費として別途積算する。 ロッド消費量は製砂1,000t当り300～700kgの範囲とする。 胴体ライナは、使用時間を勘案し、必要に応じ整備修理費に加算する。 シュートは、別途に一現場償却として積算し、スクラップ分の残存を考慮する。
胴体直径×長さ																				
018- 0924-001	900 × 2,400 mm	19	4	11,600	12.8	8,000	1,300	2,900	50	6.0	3	1,231	1,430	4,321	5,010	2,798	3,250	7,717	8,950	
1224-001	1,200 × 2,400	37	8	15,200	12.8	8,000	1,300	2,900	50	6.0	3	1,231	1,870	4,321	6,570	2,798	4,250	7,717	11,700	
1230-001	1,200 × 3,000	45	9	21,700	12.8	8,000	1,300	2,900	50	6.0	3	1,231	2,670	4,321	9,380	2,798	6,070	7,717	16,700	
1530-001	1,500 × 3,000	75	15	30,400	12.8	8,000	1,300	2,900	50	6.0	3	1,231	3,740	4,321	13,100	2,798	8,510	7,717	23,500	
1536-001	1,500 × 3,600	95	18	34,400	12.8	8,000	1,300	2,900	50	6.0	3	1,231	4,230	4,321	14,900	2,798	9,630	7,717	26,500	
1836-001	1,800 × 3,600	130	25	43,500	14.0	9,000	1,400	3,200	50	6.0	3	1,094	4,760	4,141	18,000	2,567	11,200	7,219	31,400	
1842-001	1,800 × 4,200	150	30	49,900	14.0	9,000	1,400	3,200	50	6.0	3	1,094	5,460	4,141	20,700	2,567	12,800	7,219	36,000	
2136-001	2,100 × 3,600	190	35	60,300	14.0	9,000	1,400	3,200	50	6.0	3	1,094	6,600	4,141	25,000	2,567	15,500	7,219	43,500	
2145-001	2,100 × 4,500	260	43	64,500	14.0	9,000	1,400	3,200	50	6.0	3	1,094	7,060	4,141	26,700	2,567	16,600	7,219	46,600	
2436-001	2,400 × 3,600	260	45	71,100	14.0	9,000	1,400	3,200	50	6.0	3	1,094	7,780	4,141	29,400	2,567	18,300	7,219	51,300	
2445-001	2,400 × 4,500	300	56	79,500	14.0	9,000	1,400	3,200	50	6.0	3	1,094	8,700	4,141	32,900	2,567	20,400	7,219	57,400	
2736-001	2,700 × 3,600	300	57	85,700	14.0	9,000	1,400	3,200	50	6.0	3	1,094	9,380	4,141	35,500	2,567	22,000	7,219	61,900	
2745-001	2,700 × 4,500	400	71	93,300	14.0	9,000	1,400	3,200	50	6.0	3	1,094	10,200	4,141	38,600	2,567	24,000	7,219	67,400	
4304 スクラバ																				シュート、ホッパは別途に一現場償却として積算し、スクラップ分の残存を考慮する。
胴体直径×長さ																				
018- 1530-001	1,500 × 3,000 mm	30	11	16,100	12.7	9,300	1,000	2,700	135	6.0	3	1,973	3,180	4,619	7,440	3,314	5,340	11,415	18,400	
1536-001	1,500 × 3,600	37	13	19,600	12.7	9,300	1,000	2,700	135	6.0	3	1,973	3,870	4,619	9,050	3,314	6,500	11,415	22,400	
1836-001	1,800 × 3,600	55	16	24,800	13.8	10,400	1,200	3,100	135	6.0	3	1,764	4,370	4,235	10,500	3,027	7,510	10,155	25,200	
1845-001	1,800 × 4,500	75	20	28,400	13.8	10,400	1,200	3,100	135	6.0	3	1,764	5,010	4,235	12,000	3,027	8,600	10,155	28,800	
2145-001	2,100 × 4,500	95	25	34,900	13.8	10,400	1,200	3,100	135	6.0	3	1,764	6,160	4,235	14,800	3,027	10,600	10,155	35,400	
2151-001	2,100 × 5,100	110	30	36,400	13.8	10,400	1,200	3,100	135	6.0	3	1,764	6,420	4,235	15,400	3,027	11,000	10,155	37,000	
2445-001	2,400 × 4,500	130	33	44,300	13.8	10,400	1,200	3,100	135	6.0	3	1,764	7,810	4,235	18,800	3,027	13,400	10,155	45,000	
2451-001	2,400 × 5,100	150	38	47,300	13.8	10,400	1,200	3,100	135	6.0	3	1,764	8,340	4,235	20,000	3,027	14,300	10,155	48,000	
2751-001	2,700 × 5,100	190	44	53,500	13.8	10,400	1,200	3,100	135	6.0	3	1,764	9,440	4,235	22,700	3,027	16,200	10,155	54,300	
3051-001	3,000 × 5,100	260	54	65,700	13.8	10,400	1,200	3,100	135	6.0	3	1,764	11,600	4,235	27,800	3,027	19,900	10,155	66,700	

43 骨材生産設備

分類コード	規 格				(1)	(2)	標準使用			(6)	(7)	残 存 率 (%)	運転1時間当たり		供用1日当たり		換算値				摘 要
	諸 元	機関出力 (kW)	機械 質量 (t)	基礎価格 (千円)	標準使 用 年数 (年)	(3) 運 転 時間 (時間)	(4) 運 転 日数 (日)	(5) 供用 日数 (日)	整備修 理費率 (%)	年間管 理費率 (%)	(8) 損料率 (×10-7)		(9) 損 料 (円)	(10) 損料率 (×10-7)	(11) 損 料 (円)	運転1時間当たり		供用1日当たり			
																(12) 損料率 (×10-7)	(13) 損 料 (円)	(14) 損料率 (×10-7)	(15) 損 料 (円)		
4305 分級機																					シュートは別途に一現場償却として積算し、スクラップ分の残存を考慮する。
018 〔スパイラル式・ダブルピッチ〕																					
スパイラル径×長さ																					
0540-001	450 ×	4,000 mm	1.5	1.3	3,390	12.8	8,100	810	2,900	90	6.0	3	1,710	580	4,321	1,460	3,257	1,100	9,097	3,080	
0650-001	600 ×	5,000	2.2	2.3	4,080	12.8	8,100	810	2,900	90	6.0	3	1,710	698	4,321	1,760	3,257	1,330	9,097	3,710	
0855-001	750 ×	5,500	3.7	3.5	5,220	12.8	8,100	810	2,900	90	6.0	3	1,710	893	4,321	2,260	3,257	1,700	9,097	4,750	
0965-001	900 ×	6,500	3.7	5.1	6,790	12.8	8,100	810	2,900	90	6.0	3	1,710	1,160	4,321	2,930	3,257	2,210	9,097	6,180	
1175-001	1,050 ×	7,500	5.5	6.9	8,590	14.0	9,200	890	3,200	95	6.0	3	1,560	1,340	4,141	3,560	3,000	2,580	8,625	7,410	
1280-001	1,200 ×	8,000	5.5	9.1	10,600	14.0	9,200	890	3,200	95	6.0	3	1,560	1,650	4,141	4,390	3,000	3,180	8,625	9,140	
1490-001	1,350 ×	9,000	7.5	12	12,800	14.0	9,200	890	3,200	95	6.0	3	1,560	2,000	4,141	5,300	3,000	3,840	8,625	11,000	
1590-001	1,500 ×	9,000	7.5	15	15,900	14.0	9,200	890	3,200	95	6.0	3	1,560	2,480	4,141	6,580	3,000	4,770	8,625	13,700	
1795-001	1,650 ×	9,500	11	19	17,300	14.0	9,200	890	3,200	95	6.0	3	1,560	2,700	4,141	7,160	3,000	5,190	8,625	14,900	
1810-001	1,800 ×	10,000	11	23	21,400	14.0	9,200	890	3,200	95	6.0	3	1,560	3,340	4,141	8,860	3,000	6,420	8,625	18,500	
2111-001	2,100 ×	11,000	22	27	28,300	14.0	9,200	890	3,200	95	6.0	3	1,560	4,410	4,141	11,700	3,000	8,490	8,625	24,400	
028 〔水平式バケット排出型〕																					
スパイラル径×長さ																					
3060-001	3,000 ×	6,000 mm	7	13	20,500	14.1	9,000	940	3,200	75	6.0	3	1,372	2,810	4,159	8,530	2,851	5,840	8,019	16,400	
038 〔ベルト式〕																					
ベルト幅																					
1200-001	1,200 mm		10	12	19,900	12.5	8,100	810	2,900	85	6.0	3	1,648	3,280	4,259	8,480	3,173	6,310	8,862	17,600	
4306 振動フィーダ																					吊下げ金具類を含む。60Hzの場合の作業能力は、20%増しとする。
018 〔電磁式〕																					
能力																					
0050-001	50 Hz	50 t/h	0.3	0.2	663	15.5	—	1,200	3,800	60	6.0	3	(日) 9,042	(日) 599	3,724	247	(日) 20,833	(日) 1,380	6,579	436	
0065-001	50	65	0.42	0.23	767	15.5	—	1,200	3,800	60	6.0	3	(日) 9,042	(日) 694	3,724	286	(日) 20,833	(日) 1,600	6,579	505	
0100-001	50	100	0.6	0.46	949	15.5	—	1,200	3,800	60	6.0	3	(日) 9,042	(日) 858	3,724	353	(日) 20,833	(日) 1,980	6,579	624	
0130-001	50	130	0.85	0.56	1,060	15.5	—	1,200	3,800	60	6.0	3	(日) 9,042	(日) 958	3,724	395	(日) 20,833	(日) 2,210	6,579	697	
0220-001	50	220	1.5	1	1,560	15.5	—	1,200	3,800	60	6.0	3	(日) 9,042	(日) 1,410	3,724	581	(日) 20,833	(日) 3,250	6,579	1,030	
0330-001	50	330	2.0	1.5	1,920	15.5	—	1,200	3,800	60	6.0	3	(日) 9,042	(日) 1,740	3,724	715	(日) 20,833	(日) 4,000	6,579	1,260	
0440-001	50	440	2.2	1.8	2,510	15.5	—	1,200	3,800	60	6.0	3	(日) 9,042	(日) 2,270	3,724	935	(日) 20,833	(日) 5,230	6,579	1,650	
0600-001	50	600	3.0	3.2	3,820	15.5	—	1,200	3,800	60	6.0	3	(日) 9,042	(日) 3,450	3,724	1,420	(日) 20,833	(日) 7,960	6,579	2,510	
0800-001	50	800	3.6	3.9	4,910	15.5	—	1,200	3,800	60	6.0	3	(日) 9,042	(日) 4,440	3,724	1,830	(日) 20,833	(日) 10,200	6,579	3,230	
028 〔振動電動機式〕																					
能力																					
0050-001	50 Hz	50 t/h	0.3	0.2	481	15.5	—	1,600	3,700	50	6.0	3	(日) 6,156	(日) 296	3,824	184	(日) 15,000	(日) 722	6,486	312	
0065-001	50	65	0.42	0.23	580	15.5	—	1,600	3,700	50	6.0	3	(日) 6,156	(日) 357	3,824	222	(日) 15,000	(日) 870	6,486	376	
0100-001	50	100	0.6	0.46	783	15.5	—	1,600	3,700	50	6.0	3	(日) 6,156	(日) 482	3,824	299	(日) 15,000	(日) 1,170	6,486	508	
0130-001	50	130	0.85	0.56	932	15.5	—	1,600	3,700	50	6.0	3	(日) 6,156	(日) 574	3,824	356	(日) 15,000	(日) 1,400	6,486	604	
0220-001	50	220	1.5	1.0	1,190	15.5	—	1,600	3,700	50	6.0	3	(日) 6,156	(日) 733	3,824	455	(日) 15,000	(日) 1,790	6,486	772	
0330-001	50	330	2.0	1.5	1,480	15.5	—	1,600	3,700	50	6.0	3	(日) 6,156	(日) 911	3,824	566	(日) 15,000	(日) 2,220	6,486	960	
0440-001	50	440	2.2	1.8	1,840	15.5	—	1,600	3,700	50	6.0	3	(日) 6,156	(日) 1,130	3,824	704	(日) 15,000	(日) 2,760	6,486	1,190	
0600-001	50	600	3.0	3.2	2,240	15.5	—	1,600	3,700	50	6.0	3	(日) 6,156	(日) 1,380	3,824	857	(日) 15,000	(日) 3,360	6,486	1,450	
0800-001	50	800	3.6	3.9	3,020	15.5	—	1,600	3,700	50	6.0	3	(日) 6,156	(日) 1,860	3,824	1,150	(日) 15,000	(日) 4,530	6,486	1,960	

43 骨材生産設備

分類コード	規 格				(1)	(2)	標準使用			(6)	(7)	残 存 率 (%)	運転1時間当たり		供用1日当たり		換算値				摘 要																																																																																																																																																																																																																
	諸 元	機関出力 (kW)	機械 質量 (t)	基礎価格 (千円)	標準使 用 年数 (年)	(3)	(4)	(5)	整備修 理費率 (%)	年間管 理費率 (%)	(8)		(9)	(10)	(11)	運転1時間当たり		供用1日当たり																																																																																																																																																																																																																			
						運 転 時 間 (時間)	運 転 日 数 (日)	供 用 日 数 (日)			損 料 率 (×10-7)		損 料 (円)	損 料 率 (×10-7)	損 料 (円)	(12) 損料率 (×10-7)	(13) 損 料 (円)	(14) 損料率 (×10-7)	(15) 損 料 (円)																																																																																																																																																																																																																		
038 〔機械式〕	能力 <table><tr><td>0100-001</td><td>50 Hz</td><td>100 t/h</td><td>3.7</td><td>1.8</td><td>3,870</td><td>13.0</td><td>10,200</td><td>1,100</td><td>2,500</td><td>70</td><td>6.0</td><td>3</td><td>1,162</td><td>450</td><td>5,060</td><td>1,960</td><td>2,402</td><td>930</td><td>9,800</td><td>3,790</td></tr><tr><td>0200-001</td><td>50</td><td>200</td><td>11</td><td>4.3</td><td>6,460</td><td>13.0</td><td>10,200</td><td>1,100</td><td>2,500</td><td>70</td><td>6.0</td><td>3</td><td>1,162</td><td>751</td><td>5,060</td><td>3,270</td><td>2,402</td><td>1,550</td><td>9,800</td><td>6,330</td></tr><tr><td>0300-001</td><td>50</td><td>300</td><td>15</td><td>6.2</td><td>9,060</td><td>13.0</td><td>10,200</td><td>1,100</td><td>2,500</td><td>70</td><td>6.0</td><td>3</td><td>1,162</td><td>1,050</td><td>5,060</td><td>4,580</td><td>2,402</td><td>2,180</td><td>9,800</td><td>8,880</td></tr><tr><td>0400-001</td><td>50</td><td>400</td><td>22</td><td>7.2</td><td>11,100</td><td>13.0</td><td>10,200</td><td>1,100</td><td>2,500</td><td>70</td><td>6.0</td><td>3</td><td>1,162</td><td>1,290</td><td>5,060</td><td>5,620</td><td>2,402</td><td>2,670</td><td>9,800</td><td>10,900</td></tr><tr><td>0500-001</td><td>50</td><td>500</td><td>30</td><td>11</td><td>13,200</td><td>13.0</td><td>10,200</td><td>1,100</td><td>2,500</td><td>70</td><td>6.0</td><td>3</td><td>1,162</td><td>1,530</td><td>5,060</td><td>6,680</td><td>2,402</td><td>3,170</td><td>9,800</td><td>12,900</td></tr></table>																			0100-001	50 Hz	100 t/h	3.7	1.8	3,870	13.0	10,200	1,100	2,500	70	6.0	3	1,162	450	5,060	1,960	2,402	930	9,800	3,790	0200-001	50	200	11	4.3	6,460	13.0	10,200	1,100	2,500	70	6.0	3	1,162	751	5,060	3,270	2,402	1,550	9,800	6,330	0300-001	50	300	15	6.2	9,060	13.0	10,200	1,100	2,500	70	6.0	3	1,162	1,050	5,060	4,580	2,402	2,180	9,800	8,880	0400-001	50	400	22	7.2	11,100	13.0	10,200	1,100	2,500	70	6.0	3	1,162	1,290	5,060	5,620	2,402	2,670	9,800	10,900	0500-001	50	500	30	11	13,200	13.0	10,200	1,100	2,500	70	6.0	3	1,162	1,530	5,060	6,680	2,402	3,170	9,800	12,900	60Hzの場合の作業能力は、20%増しとする。																																																																																																								
0100-001																				50 Hz	100 t/h	3.7	1.8	3,870	13.0	10,200	1,100	2,500	70	6.0	3	1,162	450	5,060	1,960	2,402	930	9,800	3,790																																																																																																																																																																																														
0200-001																				50	200	11	4.3	6,460	13.0	10,200	1,100	2,500	70	6.0	3	1,162	751	5,060	3,270	2,402	1,550	9,800	6,330																																																																																																																																																																																														
0300-001																				50	300	15	6.2	9,060	13.0	10,200	1,100	2,500	70	6.0	3	1,162	1,050	5,060	4,580	2,402	2,180	9,800	8,880																																																																																																																																																																																														
0400-001																				50	400	22	7.2	11,100	13.0	10,200	1,100	2,500	70	6.0	3	1,162	1,290	5,060	5,620	2,402	2,670	9,800	10,900																																																																																																																																																																																														
0500-001																				50	500	30	11	13,200	13.0	10,200	1,100	2,500	70	6.0	3	1,162	1,530	5,060	6,680	2,402	3,170	9,800	12,900																																																																																																																																																																																														
4307 エブロンフィーダ																																																																																																																																																																																																																																					
018 〔標準型〕	エブロン幅×長さ <table><tr><td>0615-001</td><td>600 ×</td><td>1,500 mm</td><td>2.2</td><td>1.9</td><td>5,140</td><td>14.1</td><td>11,400</td><td>1,200</td><td>2,800</td><td>105</td><td>6.0</td><td>3</td><td>1,346</td><td>692</td><td>4,754</td><td>2,440</td><td>2,514</td><td>1,290</td><td>10,236</td><td>5,260</td></tr><tr><td>0715-001</td><td>700 ×</td><td>1,500</td><td>2.2</td><td>2.1</td><td>5,480</td><td>14.1</td><td>11,400</td><td>1,200</td><td>2,800</td><td>105</td><td>6.0</td><td>3</td><td>1,346</td><td>738</td><td>4,754</td><td>2,610</td><td>2,514</td><td>1,380</td><td>10,236</td><td>5,610</td></tr><tr><td>0820-001</td><td>800 ×</td><td>2,000</td><td>2.2</td><td>2.7</td><td>6,460</td><td>14.1</td><td>11,400</td><td>1,200</td><td>2,800</td><td>105</td><td>6.0</td><td>3</td><td>1,346</td><td>870</td><td>4,754</td><td>3,070</td><td>2,514</td><td>1,620</td><td>10,236</td><td>6,610</td></tr><tr><td>0920-001</td><td>900 ×</td><td>2,000</td><td>3.7</td><td>3</td><td>7,330</td><td>14.1</td><td>11,400</td><td>1,200</td><td>2,800</td><td>105</td><td>6.0</td><td>3</td><td>1,346</td><td>987</td><td>4,754</td><td>3,480</td><td>2,514</td><td>1,840</td><td>10,236</td><td>7,500</td></tr><tr><td>1025-001</td><td>1,000 ×</td><td>2,500</td><td>3.7</td><td>4.1</td><td>8,240</td><td>14.1</td><td>11,400</td><td>1,200</td><td>2,800</td><td>105</td><td>6.0</td><td>3</td><td>1,346</td><td>1,110</td><td>4,754</td><td>3,920</td><td>2,514</td><td>2,070</td><td>10,236</td><td>8,430</td></tr><tr><td>1125-001</td><td>1,100 ×</td><td>2,500</td><td>3.7</td><td>4.4</td><td>9,970</td><td>14.1</td><td>11,400</td><td>1,200</td><td>2,800</td><td>105</td><td>6.0</td><td>3</td><td>1,346</td><td>1,340</td><td>4,754</td><td>4,740</td><td>2,514</td><td>2,510</td><td>10,236</td><td>10,200</td></tr><tr><td>1225-001</td><td>1,200 ×</td><td>2,500</td><td>5.5</td><td>4.8</td><td>11,300</td><td>14.1</td><td>11,400</td><td>1,200</td><td>2,800</td><td>105</td><td>6.0</td><td>3</td><td>1,346</td><td>1,520</td><td>4,754</td><td>5,370</td><td>2,514</td><td>2,840</td><td>10,236</td><td>11,600</td></tr><tr><td>1230-001</td><td>1,200 ×</td><td>3,000</td><td>5.5</td><td>5.4</td><td>12,200</td><td>14.1</td><td>11,400</td><td>1,200</td><td>2,800</td><td>105</td><td>6.0</td><td>3</td><td>1,346</td><td>1,640</td><td>4,754</td><td>5,800</td><td>2,514</td><td>3,070</td><td>10,236</td><td>12,500</td></tr><tr><td>1440-001</td><td>1,400 ×</td><td>4,000</td><td>5.5</td><td>7.1</td><td>14,200</td><td>14.1</td><td>11,400</td><td>1,200</td><td>2,800</td><td>105</td><td>6.0</td><td>3</td><td>1,346</td><td>1,910</td><td>4,754</td><td>6,750</td><td>2,514</td><td>3,570</td><td>10,236</td><td>14,500</td></tr><tr><td>1530-001</td><td>1,500 ×</td><td>3,000</td><td>5.5</td><td>6.7</td><td>13,500</td><td>14.1</td><td>11,400</td><td>1,200</td><td>2,800</td><td>105</td><td>6.0</td><td>3</td><td>1,346</td><td>1,820</td><td>4,754</td><td>6,420</td><td>2,514</td><td>3,390</td><td>10,236</td><td>13,800</td></tr></table>																			0615-001	600 ×	1,500 mm	2.2	1.9	5,140	14.1	11,400	1,200	2,800	105	6.0	3	1,346	692	4,754	2,440	2,514	1,290	10,236	5,260	0715-001	700 ×	1,500	2.2	2.1	5,480	14.1	11,400	1,200	2,800	105	6.0	3	1,346	738	4,754	2,610	2,514	1,380	10,236	5,610	0820-001	800 ×	2,000	2.2	2.7	6,460	14.1	11,400	1,200	2,800	105	6.0	3	1,346	870	4,754	3,070	2,514	1,620	10,236	6,610	0920-001	900 ×	2,000	3.7	3	7,330	14.1	11,400	1,200	2,800	105	6.0	3	1,346	987	4,754	3,480	2,514	1,840	10,236	7,500	1025-001	1,000 ×	2,500	3.7	4.1	8,240	14.1	11,400	1,200	2,800	105	6.0	3	1,346	1,110	4,754	3,920	2,514	2,070	10,236	8,430	1125-001	1,100 ×	2,500	3.7	4.4	9,970	14.1	11,400	1,200	2,800	105	6.0	3	1,346	1,340	4,754	4,740	2,514	2,510	10,236	10,200	1225-001	1,200 ×	2,500	5.5	4.8	11,300	14.1	11,400	1,200	2,800	105	6.0	3	1,346	1,520	4,754	5,370	2,514	2,840	10,236	11,600	1230-001	1,200 ×	3,000	5.5	5.4	12,200	14.1	11,400	1,200	2,800	105	6.0	3	1,346	1,640	4,754	5,800	2,514	3,070	10,236	12,500	1440-001	1,400 ×	4,000	5.5	7.1	14,200	14.1	11,400	1,200	2,800	105	6.0	3	1,346	1,910	4,754	6,750	2,514	3,570	10,236	14,500	1530-001	1,500 ×	3,000	5.5	6.7	13,500	14.1	11,400	1,200	2,800	105	6.0	3	1,346	1,820	4,754	6,420	2,514	3,390	10,236	13,800
0615-001																				600 ×	1,500 mm	2.2	1.9	5,140	14.1	11,400	1,200	2,800	105	6.0	3	1,346	692	4,754	2,440	2,514	1,290	10,236	5,260																																																																																																																																																																																														
0715-001																				700 ×	1,500	2.2	2.1	5,480	14.1	11,400	1,200	2,800	105	6.0	3	1,346	738	4,754	2,610	2,514	1,380	10,236	5,610																																																																																																																																																																																														
0820-001																				800 ×	2,000	2.2	2.7	6,460	14.1	11,400	1,200	2,800	105	6.0	3	1,346	870	4,754	3,070	2,514	1,620	10,236	6,610																																																																																																																																																																																														
0920-001																				900 ×	2,000	3.7	3	7,330	14.1	11,400	1,200	2,800	105	6.0	3	1,346	987	4,754	3,480	2,514	1,840	10,236	7,500																																																																																																																																																																																														
1025-001																				1,000 ×	2,500	3.7	4.1	8,240	14.1	11,400	1,200	2,800	105	6.0	3	1,346	1,110	4,754	3,920	2,514	2,070	10,236	8,430																																																																																																																																																																																														
1125-001																				1,100 ×	2,500	3.7	4.4	9,970	14.1	11,400	1,200	2,800	105	6.0	3	1,346	1,340	4,754	4,740	2,514	2,510	10,236	10,200																																																																																																																																																																																														
1225-001																				1,200 ×	2,500	5.5	4.8	11,300	14.1	11,400	1,200	2,800	105	6.0	3	1,346	1,520	4,754	5,370	2,514	2,840	10,236	11,600																																																																																																																																																																																														
1230-001																				1,200 ×	3,000	5.5	5.4	12,200	14.1	11,400	1,200	2,800	105	6.0	3	1,346	1,640	4,754	5,800	2,514	3,070	10,236	12,500																																																																																																																																																																																														
1440-001																				1,400 ×	4,000	5.5	7.1	14,200	14.1	11,400	1,200	2,800	105	6.0	3	1,346	1,910	4,754	6,750	2,514	3,570	10,236	14,500																																																																																																																																																																																														
1530-001	1,500 ×	3,000	5.5	6.7	13,500	14.1	11,400	1,200	2,800	105	6.0	3	1,346	1,820	4,754	6,420	2,514	3,390	10,236	13,800																																																																																																																																																																																																																	
028 〔特重型〕																																																																																																																																																																																																																																					
エブロン幅×長さ <table><tr><td>0825-001</td><td>800 ×</td><td>2,500 mm</td><td>2.2</td><td>5.5</td><td>8,290</td><td>13.0</td><td>10,200</td><td>1,100</td><td>2,500</td><td>45</td><td>6.0</td><td>3</td><td>917</td><td>760</td><td>5,060</td><td>4,190</td><td>2,157</td><td>1,790</td><td>8,800</td><td>7,300</td></tr><tr><td>0925-001</td><td>900 ×</td><td>2,500</td><td>3.7</td><td>6.2</td><td>9,100</td><td>13.0</td><td>10,200</td><td>1,100</td><td>2,500</td><td>45</td><td>6.0</td><td>3</td><td>917</td><td>834</td><td>5,060</td><td>4,600</td><td>2,157</td><td>1,960</td><td>8,800</td><td>8,010</td></tr><tr><td>1030-001</td><td>1,000 ×</td><td>3,000</td><td>3.7</td><td>9.8</td><td>13,500</td><td>13.0</td><td>10,200</td><td>1,100</td><td>2,500</td><td>45</td><td>6.0</td><td>3</td><td>917</td><td>1,240</td><td>5,060</td><td>6,830</td><td>2,157</td><td>2,910</td><td>8,800</td><td>11,900</td></tr><tr><td>1035-001</td><td>1,000 ×</td><td>3,500</td><td>3.7</td><td>10</td><td>14,300</td><td>13.0</td><td>10,200</td><td>1,100</td><td>2,500</td><td>45</td><td>6.0</td><td>3</td><td>917</td><td>1,310</td><td>5,060</td><td>7,240</td><td>2,157</td><td>3,080</td><td>8,800</td><td>12,600</td></tr><tr><td>1245-001</td><td>1,200 ×</td><td>4,500</td><td>5.5</td><td>14</td><td>18,600</td><td>14.1</td><td>11,400</td><td>1,200</td><td>2,800</td><td>55</td><td>6.0</td><td>3</td><td>908</td><td>1,690</td><td>4,754</td><td>8,840</td><td>2,075</td><td>3,860</td><td>8,450</td><td>15,700</td></tr><tr><td>1440-001</td><td>1,400 ×</td><td>4,000</td><td>5.5</td><td>16</td><td>21,600</td><td>14.1</td><td>11,400</td><td>1,200</td><td>2,800</td><td>55</td><td>6.0</td><td>3</td><td>908</td><td>1,960</td><td>4,754</td><td>10,300</td><td>2,075</td><td>4,480</td><td>8,450</td><td>18,300</td></tr><tr><td>1450-001</td><td>1,400 ×</td><td>5,000</td><td>7.5</td><td>18</td><td>23,500</td><td>14.1</td><td>11,400</td><td>1,200</td><td>2,800</td><td>55</td><td>6.0</td><td>3</td><td>908</td><td>2,130</td><td>4,754</td><td>11,200</td><td>2,075</td><td>4,880</td><td>8,450</td><td>19,900</td></tr><tr><td>1540-001</td><td>1,500 ×</td><td>4,000</td><td>7.5</td><td>21</td><td>25,100</td><td>14.1</td><td>11,400</td><td>1,200</td><td>2,800</td><td>55</td><td>6.0</td><td>3</td><td>908</td><td>2,280</td><td>4,754</td><td>11,900</td><td>2,075</td><td>5,210</td><td>8,450</td><td>21,200</td></tr><tr><td>1650-001</td><td>1,600 ×</td><td>5,000</td><td>11</td><td>23</td><td>29,700</td><td>14.1</td><td>11,400</td><td>1,200</td><td>2,800</td><td>55</td><td>6.0</td><td>3</td><td>908</td><td>2,700</td><td>4,754</td><td>14,100</td><td>2,075</td><td>6,160</td><td>8,450</td><td>25,100</td></tr><tr><td>1660-001</td><td>1,600 ×</td><td>6,000</td><td>15</td><td>25</td><td>32,300</td><td>14.1</td><td>11,400</td><td>1,200</td><td>2,800</td><td>55</td><td>6.0</td><td>3</td><td>908</td><td>2,930</td><td>4,754</td><td>15,400</td><td>2,075</td><td>6,700</td><td>8,450</td><td>27,300</td></tr></table>																			0825-001	800 ×	2,500 mm	2.2	5.5	8,290	13.0	10,200	1,100	2,500	45	6.0	3	917	760	5,060	4,190	2,157	1,790	8,800	7,300	0925-001	900 ×	2,500	3.7	6.2	9,100	13.0	10,200	1,100	2,500	45	6.0	3	917	834	5,060	4,600	2,157	1,960	8,800	8,010	1030-001	1,000 ×	3,000	3.7	9.8	13,500	13.0	10,200	1,100	2,500	45	6.0	3	917	1,240	5,060	6,830	2,157	2,910	8,800	11,900	1035-001	1,000 ×	3,500	3.7	10	14,300	13.0	10,200	1,100	2,500	45	6.0	3	917	1,310	5,060	7,240	2,157	3,080	8,800	12,600	1245-001	1,200 ×	4,500	5.5	14	18,600	14.1	11,400	1,200	2,800	55	6.0	3	908	1,690	4,754	8,840	2,075	3,860	8,450	15,700	1440-001	1,400 ×	4,000	5.5	16	21,600	14.1	11,400	1,200	2,800	55	6.0	3	908	1,960	4,754	10,300	2,075	4,480	8,450	18,300	1450-001	1,400 ×	5,000	7.5	18	23,500	14.1	11,400	1,200	2,800	55	6.0	3	908	2,130	4,754	11,200	2,075	4,880	8,450	19,900	1540-001	1,500 ×	4,000	7.5	21	25,100	14.1	11,400	1,200	2,800	55	6.0	3	908	2,280	4,754	11,900	2,075	5,210	8,450	21,200	1650-001	1,600 ×	5,000	11	23	29,700	14.1	11,400	1,200	2,800	55	6.0	3	908	2,700	4,754	14,100	2,075	6,160	8,450	25,100	1660-001	1,600 ×	6,000	15	25	32,300	14.1	11,400	1,200	2,800	55	6.0	3	908	2,930	4,754	15,400	2,075	6,700	8,450	27,300	
																			0825-001	800 ×	2,500 mm	2.2	5.5	8,290	13.0	10,200	1,100	2,500	45	6.0	3	917	760	5,060	4,190	2,157	1,790	8,800	7,300																																																																																																																																																																																														
																			0925-001	900 ×	2,500	3.7	6.2	9,100	13.0	10,200	1,100	2,500	45	6.0	3	917	834	5,060	4,600	2,157	1,960	8,800	8,010																																																																																																																																																																																														
																			1030-001	1,000 ×	3,000	3.7	9.8	13,500	13.0	10,200	1,100	2,500	45	6.0	3	917	1,240	5,060	6,830	2,157	2,910	8,800	11,900																																																																																																																																																																																														
																			1035-001	1,000 ×	3,500	3.7	10	14,300	13.0	10,200	1,100	2,500	45	6.0	3	917	1,310	5,060	7,240	2,157	3,080	8,800	12,600																																																																																																																																																																																														
																			1245-001	1,200 ×	4,500	5.5	14	18,600	14.1	11,400	1,200	2,800	55	6.0	3	908	1,690	4,754	8,840	2,075	3,860	8,450	15,700																																																																																																																																																																																														
																			1440-001	1,400 ×	4,000	5.5	16	21,600	14.1	11,400	1,200	2,800	55	6.0	3	908	1,960	4,754	10,300	2,075	4,480	8,450	18,300																																																																																																																																																																																														
																			1450-001	1,400 ×	5,000	7.5	18	23,500	14.1	11,400	1,200	2,800	55	6.0	3	908	2,130	4,754	11,200	2,075	4,880	8,450	19,900																																																																																																																																																																																														
																			1540-001	1,500 ×	4,000	7.5	21	25,100	14.1	11,400	1,200	2,800	55	6.0	3	908	2,280	4,754	11,900	2,075	5,210	8,450	21,200																																																																																																																																																																																														
																			1650-001	1,600 ×	5,000	11	23	29,700	14.1	11,400	1,200	2,800	55	6.0	3	908	2,700	4,754	14,100	2,075	6,160	8,450	25,100																																																																																																																																																																																														
1660-001	1,600 ×	6,000	15	25	32,300	14.1	11,400	1,200	2,800	55	6.0	3	908	2,930	4,754	15,400	2,075	6,700	8,450	27,300																																																																																																																																																																																																																	

43 骨材生産設備

分類コード	規 格				(1)	(2)	標準使用			(6)	(7)	残 存 率 (%)	運転1時間当たり		供用1日当たり		換算値				摘 要
	諸 元	機関出力 (kW)	機械 質量 (t)	基礎価格 (千円)	標準使 用 年数 (年)	(3)	(4)	(5)	整備修 理費率 (%)	年間管 理費率 (%)	(8)		(9)	(10)	(11)	運転1時間当たり		供用1日当たり			
						運転 時間 (時間)	運転 日数 (日)	供用 日数 (日)			損料率 (×10-7)		損 料 (円)	損料率 (×10-7)	損 料 (円)	(12) 損料率 (×10-7)	(13) 損 料 (円)	(14) 損料率 (×10-7)	(15) 損 料 (円)		
4308 振動ふるい																					整備修理費率には、スクリーンプレート、ワイヤクロス及びラバースクリーンの取替費を含む。 シュートは、別途に一現場償却として積算し、スクラップ分の残存を考慮する。 単床式の損料は、二床式損料の10%減とし、特重型の損料は標準型損料の30%増しとする。
018 〔傾斜標準型二床式〕																					
振動枠幅×長さ																					
0918-001	900 ×	1,800 mm	3.7	1.9	3,920	12.7	9,300	1,200	2,700	110	6.0	3	1,704	668	4,619	1,810	3,045	1,190	10,489	4,110	
0924-001	900 ×	2,400	3.7	2.2	4,250	12.7	9,300	1,200	2,700	110	6.0	3	1,704	724	4,619	1,960	3,045	1,290	10,489	4,460	
1224-001	1,200 ×	2,400	5.5	2.6	4,740	12.7	9,300	1,200	2,700	110	6.0	3	1,704	808	4,619	2,190	3,045	1,440	10,489	4,970	
1230-001	1,200 ×	3,000	7.5	2.9	5,260	12.7	9,300	1,200	2,700	110	6.0	3	1,704	896	4,619	2,430	3,045	1,600	10,489	5,520	
1530-001	1,500 ×	3,000	7.5	3.9	6,200	13.8	10,400	1,300	3,100	125	6.0	3	1,668	1,030	4,235	2,630	2,931	1,820	9,832	6,100	
1536-001	1,500 ×	3,600	11	4.2	6,620	13.8	10,400	1,300	3,100	125	6.0	3	1,668	1,100	4,235	2,800	2,931	1,940	9,832	6,510	
1542-001	1,500 ×	4,200	11	4.7	7,060	13.8	10,400	1,300	3,100	125	6.0	3	1,668	1,180	4,235	2,990	2,931	2,070	9,832	6,940	
1842-001	1,800 ×	4,200	15	5	7,680	13.8	10,400	1,300	3,100	125	6.0	3	1,668	1,280	4,235	3,250	2,931	2,250	9,832	7,550	
1848-001	1,800 ×	4,800	15	5.8	8,280	13.8	10,400	1,300	3,100	125	6.0	3	1,668	1,380	4,235	3,510	2,931	2,430	9,832	8,140	
2148-001	2,100 ×	4,800	22	7.7	10,800	13.8	10,400	1,300	3,100	125	6.0	3	1,668	1,800	4,235	4,570	2,931	3,170	9,832	10,600	
2160-001	2,100 ×	6,000	22	10	13,500	13.8	10,400	1,300	3,100	125	6.0	3	1,668	2,250	4,235	5,720	2,931	3,960	9,832	13,300	
2460-001	2,400 ×	6,000	30	11	14,500	13.8	10,400	1,300	3,100	125	6.0	3	1,668	2,420	4,235	6,140	2,931	4,250	9,832	14,300	
2466-001	2,400 ×	6,600	37	13	14,900	13.8	10,400	1,300	3,100	125	6.0	3	1,668	2,490	4,235	6,310	2,931	4,370	9,832	14,600	
028 〔水平標準型二床式〕																					
振動枠幅×長さ																					
0918-001	900 ×	1,800 mm	5.5	2.4	3,910	12.7	8,200	880	2,700	85	6.0	3	1,628	637	4,619	1,810	3,149	1,230	9,563	3,740	
0924-001	900 ×	2,400	5.5	2.7	4,330	12.7	8,200	880	2,700	85	6.0	3	1,628	705	4,619	2,000	3,149	1,360	9,563	4,140	
1224-001	1,200 ×	2,400	5.5	3.5	5,130	12.7	8,200	880	2,700	85	6.0	3	1,628	835	4,619	2,370	3,149	1,620	9,563	4,910	
1230-001	1,200 ×	3,000	5.5	3.8	5,710	12.7	8,200	880	2,700	85	6.0	3	1,628	930	4,619	2,640	3,149	1,800	9,563	5,460	
1530-001	1,500 ×	3,000	7.5	4.5	6,630	13.8	9,000	920	3,100	90	6.0	3	1,539	1,020	4,235	2,810	2,998	1,990	8,703	5,770	
1536-001	1,500 ×	3,600	11	5.2	7,170	13.8	9,000	920	3,100	90	6.0	3	1,539	1,100	4,235	3,040	2,998	2,150	8,703	6,240	
1542-001	1,500 ×	4,200	15	5.9	7,920	13.8	9,000	920	3,100	90	6.0	3	1,539	1,220	4,235	3,350	2,998	2,370	8,703	6,890	
1842-001	1,800 ×	4,200	19	7.1	9,660	13.8	9,000	920	3,100	90	6.0	3	1,539	1,490	4,235	4,090	2,998	2,900	8,703	8,410	
1848-001	1,800 ×	4,800	19	8.8	11,400	13.8	9,000	920	3,100	90	6.0	3	1,539	1,750	4,235	4,830	2,998	3,420	8,703	9,920	
2148-001	2,100 ×	4,800	22	10	14,200	13.8	9,000	920	3,100	90	6.0	3	1,539	2,190	4,235	6,010	2,998	4,260	8,703	12,400	
2160-001	2,100 ×	6,000	30	12	16,300	13.8	9,000	920	3,100	90	6.0	3	1,539	2,510	4,235	6,900	2,998	4,890	8,703	14,200	
2460-001	2,400 ×	6,000	37	14	18,400	13.8	9,000	920	3,100	90	6.0	3	1,539	2,830	4,235	7,790	2,998	5,520	8,703	16,000	
2466-001	2,400 ×	6,600	45	15	19,100	13.8	9,000	920	3,100	90	6.0	3	1,539	2,940	4,235	8,090	2,998	5,730	8,703	16,600	

43 骨材生産設備

分類コード	規 格			(1) 基礎価格 (千円)	(2) 標準使 用 年数 (年)	標準使用			(6) 整備修 理費率 (%)	(7) 年間管 理費率 (%)	残 存 率 (%)	運転1時間当たり		供用1日当たり		換算値				摘 要	
	諸 元	機関出力 (kW)	機械 質量 (t)			(3) 運転 時間 (時間)	(4) 運転 日数 (日)	(5) 供用 日数 (日)				(8) 損料率 (×10-7)	(9) 損 料 (円)	(10) 損料率 (×10-7)	(11) 損 料 (円)	運転1時間当たり		供用1日当たり			
																(12) 損料率 (×10-7)	(13) 損 料 (円)	(14) 損料率 (×10-7)	(15) 損 料 (円)		
4309 ベルトコンベヤ																					
018- 0045-001	ベルト幅機長 450mm区分	10m当たり																			
	0～15m 15mまで	—	—	2, 140	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	256	5, 179	1, 110	2, 673	572	9, 357	2, 000	ベルトコンベヤの損料にはフレームを含み 脚及びロックラダーを含まない。 トリップバ(自走式両側排出型)を付ける場合は、 基礎価格にそれぞれ次の価格を加算する。 ベルト幅(mm) 加算額(千円) 450 4,180 600 4,850 750 5,350 900 5,850 1,050 6,550 1,200 7,830 シュート、ホツバは別途に一現場消却として 積算し、スクラップ分の残存を考慮する。	
	15～30 15超過分	—	—	986	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	118	5, 179	511	2, 673	264	9, 357	923		
	30～50 30超過分	—	—	757	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	90	5, 179	392	2, 673	202	9, 357	708		
50以上 50超過分	—	—	574	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	69	5, 179	297	2, 673	153	9, 357	537			
0060-001	ベルト幅機長 600mm区分																				
	0～15m 15mまで	—	—	2, 760	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	330	5, 179	1, 430	2, 673	738	9, 357	2, 580		
	15～30 15超過分	—	—	1, 220	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	146	5, 179	632	2, 673	326	9, 357	1, 140		
	30～50 30超過分	—	—	892	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	107	5, 179	462	2, 673	238	9, 357	835		
0075-001	ベルト幅機長 750mm区分																				
	0～15m 15mまで	—	—	3, 580	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	427	5, 179	1, 850	2, 673	957	9, 357	3, 350		
	15～30 15超過分	—	—	1, 410	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	168	5, 179	730	2, 673	377	9, 357	1, 320		
	30～50 30超過分	—	—	1, 020	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	122	5, 179	528	2, 673	273	9, 357	954		
0090-001	ベルト幅機長 900mm区分																				
	0～15m 15mまで	—	—	4, 310	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	515	5, 179	2, 230	2, 673	1, 150	9, 357	4, 030		
	15～30 15超過分	—	—	1, 710	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	204	5, 179	886	2, 673	457	9, 357	1, 600		
	30～50 30超過分	—	—	1, 260	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	150	5, 179	653	2, 673	337	9, 357	1, 180		
0105-001	ベルト幅機長 1, 050mm区分																				
	0～15m 15mまで	—	—	5, 300	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	633	5, 179	2, 740	2, 673	1, 420	9, 357	4, 960		
	15～30 15超過分	—	—	2, 040	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	244	5, 179	1, 060	2, 673	545	9, 357	1, 910		
	30～50 30超過分	—	—	1, 470	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	176	5, 179	761	2, 673	393	9, 357	1, 380		
0120-001	ベルト幅機長 1, 200mm区分																				
	0～15m 15mまで	—	—	5, 900	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	704	5, 179	3, 060	2, 673	1, 580	9, 357	5, 520		
	15～30 15超過分	—	—	2, 270	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	271	5, 179	1, 180	2, 673	607	9, 357	2, 120		
	30～50 30超過分	—	—	1, 620	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	193	5, 179	839	2, 673	433	9, 357	1, 520		
	50以上 50超過分	—	—	1, 130	4. 0	4, 900	640	1, 400	10	6. 0	3	1, 194	135	5, 179	585	2, 673	302	9, 357	1, 060		

44 セメント輸送及び貯蔵設備

分類コード	規 格			(1)	(2)	標準使用			(6)	(7)	残 存 率 (%)	運転1時間当たり		供用1日当たり		換算値				摘 要	
	諸 元	機関出力 (kW)	機械 質量 (t)	基礎価格 (千円)	標準使 用 年数 (年)	(3) 運転 時間 (時間)	(4) 運転 日数 (日)	(5) 供用 日数 (日)	整備修 理費率 (%)	年間管 理費率 (%)		(8) 損料率 (×10-7)	(9) 損 料 (円)	(10) 損料率 (×10-7)	(11) 損 料 (円)	運転1時間当たり		供用1日当たり			
																(12) 損料率 (×10-7)	(13) 損 料 (円)	(14) 損料率 (×10-7)	(15) 損 料 (円)		
44 セメント輸送及び貯蔵設備																					
4401 スクリュコンベヤ																					
018 〔水平型〕																					
	能力		7m当たり	7m当たり																	
2010-001	20 t/h	2.2	1	786	7.9	5,800	740	1,400	10	6.0	3	1,009	79	6,850	538	2,662	209	11,029	867	ギヤードモータを含む。水平型とは、傾斜角10° 以下をいう。	
3010-001	30	3.7	1	847	7.9	5,800	740	1,400	10	6.0	3	1,009	85	6,850	580	2,662	225	11,029	934		
4010-001	40	5.5	1.1	998	7.9	5,800	740	1,400	10	6.0	3	1,009	101	6,850	684	2,662	266	11,029	1,100		
5010-001	50	5.5	1.2	1,090	7.9	5,800	740	1,400	10	6.0	3	1,009	110	6,850	747	2,662	290	11,029	1,200		
6010-001	60	7.5	1.3	1,260	7.9	5,800	740	1,400	10	6.0	3	1,009	127	6,850	863	2,662	335	11,029	1,390		
8010-001	80	11	1.4	1,480	7.9	5,800	740	1,400	10	6.0	3	1,009	149	6,850	1,010	2,662	394	11,029	1,630		
4402 バケットエレベータ																					
018 〔ベルト型〕																					
	能力		10m当たり	10m当たり																	
0200-001	20 t/h	3.7	2.9	1,910	7.9	5,300	690	1,300	20	6.0	3	1,292	247	7,377	1,410	3,102	592	12,646	2,420	シュート、ギヤードモータを含む。	
0300-001	30	5.5	3.1	2,010	7.9	5,300	690	1,300	20	6.0	3	1,292	260	7,377	1,480	3,102	624	12,646	2,540		
0400-001	40	7.5	3.2	2,110	7.9	5,300	690	1,300	20	6.0	3	1,292	273	7,377	1,560	3,102	655	12,646	2,670		
0500-001	50	11	3.5	2,230	7.9	5,300	690	1,300	20	6.0	3	1,292	288	7,377	1,650	3,102	692	12,646	2,820		
0600-001	60	11	3.9	2,330	7.9	5,300	690	1,300	20	6.0	3	1,292	301	7,377	1,720	3,102	723	12,646	2,950		
0800-001	80	15	4.1	2,670	7.9	5,300	690	1,300	20	6.0	3	1,292	345	7,377	1,970	3,102	828	12,646	3,380		
4403 セメント空気輸送機																					
018 〔ブロワ式〕																					
0001-001	各種	—	—	—	10.9	11,700	1,100	2,700	45	6.0	3	799	—	4,219	—	1,773	—	7,681	—		
4404 セメントサイロ																					
018 〔鋼製溶接構造〕																					
	容量	排出能力																			
0032-001	30 t	20 t/h	0.75	4.5	3,070	9.4	—	—	2,000	25	6.0	3	—	—	8,920	2,740	—	—	8,920	2,740	ロータリフィーダ、レベルスイッチ、エアレーション装置及びバグフィルタを含み、スクリュコンベヤ、バケットエレベータは含まない。
0052-001	50	20	0.75	6.2	4,020	9.4	—	—	2,000	25	6.0	3	—	—	8,920	3,590	—	—	8,920	3,590	
0130-001	100	30	0.75	10	5,540	9.4	—	—	2,000	25	6.0	3	—	—	8,920	4,940	—	—	8,920	4,940	
0230-001	200	30	0.75	16	8,840	9.4	—	—	2,000	25	6.0	3	—	—	8,920	7,890	—	—	8,920	7,890	
0330-001	300	30	0.75	22	11,400	9.4	—	—	2,000	25	6.0	3	—	—	8,920	10,200	—	—	8,920	10,200	
0440-001	400	40	0.75	30	15,400	9.4	—	—	2,000	25	6.0	3	—	—	8,920	13,700	—	—	8,920	13,700	
0540-001	500	40	0.75	38	18,900	9.4	—	—	2,000	25	6.0	3	—	—	8,920	16,900	—	—	8,920	16,900	
0640-001	600	40	0.75	42	20,600	9.4	—	—	2,000	25	6.0	3	—	—	8,920	18,400	—	—	8,920	18,400	
0860-001	800	60	1.5	54	25,700	9.4	—	—	2,000	25	6.0	3	—	—	8,920	22,900	—	—	8,920	22,900	
1060-001	1,000	60	1.5	69	32,400	9.4	—	—	2,000	25	6.0	3	—	—	8,920	28,900	—	—	8,920	28,900	
1560-001	1,500	60	1.5	100	45,100	9.4	—	—	2,000	25	6.0	3	—	—	8,920	40,200	—	—	8,920	40,200	

45 給水設備

分類コード	規 格			(1) 基礎価格 (千円)	(2) 標準使 用 年数 (年)	標準使用			(6) 整備修 理費率 (%)	(7) 年間管 理費率 (%)	残 存 率 (%)	運転1時間当たり		供用1日当たり		換算値				摘 要		
	諸 元	機関出力 (kW)	機械 質量 (t)			(3) 運転 時間 (時間)	(4) 運転 日数 (日)	(5) 供用 日数 (日)				(8) 損料率 (×10-7)	(9) 損 料 (円)	(10) 損料率 (×10-7)	(11) 損 料 (円)	運転1時間当たり		供用1日当たり				
																(12) 損料率 (×10-7)	(13) 損 料 (円)	(14) 損料率 (×10-7)	(15) 損 料 (円)			
45 給水設備																				ベース、電動機、起動機、バルブ類を含み、 配管は含まない。 損料は、清水用に使用する場合とする。		
4501 渦巻ポンプ																						
口径 全揚程																						
018-	2009-001	200 mm	9 m	11	0.77	2,020	6.9	15,300	1,500	2,100	30	6.0	3	513	104	4,281	865	1,101	222		8,019	1,620
	2015-001	200	15	18.5	0.88	2,400	6.9	15,300	1,500	2,100	30	6.0	3	513	123	4,281	1,030	1,101	264		8,019	1,920
	2025-001	200	25	30	1	3,090	6.9	15,300	1,500	2,100	30	6.0	3	513	159	4,281	1,320	1,101	340		8,019	2,480
	2509-001	250	9	18.5	1.1	3,100	6.9	15,300	1,500	2,100	30	6.0	3	513	159	4,281	1,330	1,101	341		8,019	2,490
	2515-001	250	14.5	30	1.3	3,480	6.9	15,300	1,500	2,100	30	6.0	3	513	179	4,281	1,490	1,101	383		8,019	2,790
	2527-001	250	27	55	1.6	7,070	6.9	15,300	1,500	2,100	30	6.0	3	513	363	4,281	3,030	1,101	778		8,019	5,670
	3012-001	300	12	30	1.6	3,980	6.9	15,300	1,500	2,100	30	6.0	3	513	204	4,281	1,700	1,101	438		8,019	3,190
	3022-001	300	22	55	1.9	7,480	6.9	15,300	1,500	2,100	30	6.0	3	513	384	4,281	3,200	1,101	824		8,019	6,000
	3037-001	300	37	95	2.1	10,700	6.9	15,300	1,500	2,100	30	6.0	3	513	549	4,281	4,580	1,101	1,180	8,019	8,580	
	3053-001	300	53	150	2.5	14,500	6.9	15,300	1,500	2,100	30	6.0	3	513	744	4,281	6,210	1,101	1,600	8,019	11,600	
4502 多段式ポンプ																						
018-	0001-001	各種		—	—	—	6.9	15,300	1,500	2,100	30	6.0	3	513	—	4,281	—	1,101	—		8,019	—

46 公害対策設備

分類コード	規 格			(1)	(2)	標準使用			(6)	(7)	残 存 率 (%)	運転1時間当たり		供用1日当たり		換算値				摘 要
	諸 元	機関出力 (kW)	機械 質量 (t)	基礎価格 (千円)	標準使 用 年数 (年)	(3)	(4)	(5)	整備修 理費率 (%)	年間管 理費率 (%)		(8)	(9)	(10)	(11)	運転1時間当たり		供用1日当たり		
						運 転 時 間 (時間)	運 転 日 数 (日)	供用 日 数 (日)				損料率 (×10-7)	損 料 (円)	損料率 (×10-7)	損 料 (円)	(12) 損料率 (×10-7)	(13) 損 料 (円)	(14) 損料率 (×10-7)	(15) 損 料 (円)	
46 公害対策設備																				建屋、薬品供給装置、攪拌槽、原水ポンプ、 排泥ポンプ(輸送距離10m)を含み、原水 送水用トイ、原水槽、排泥配管、脱水機、 中和装置等は含まない。
4601 濁水処理プラント（骨材プラント用）																				
018 〔丸型シクナ・鋼板製〕																				
処理能力																				
0100-001	100 m ³ /h	38	35	41,500	10.0	17,600	1,500	2,600	35	6.0	3	474	1,970	4,173	17,300	1,091	4,530	7,385	30,600	
0150-001	150	45	40	49,000	10.0	17,600	1,500	2,600	35	6.0	3	474	2,320	4,173	20,400	1,091	5,350	7,385	36,200	
0200-001	200	60	51	57,500	10.0	17,600	1,500	2,600	35	6.0	3	474	2,730	4,173	24,000	1,091	6,270	7,385	42,500	
0250-001	250	66	60	63,100	10.0	17,600	1,500	2,600	35	6.0	3	474	2,990	4,173	26,300	1,091	6,880	7,385	46,600	
0300-001	300	86	66	72,800	10.0	17,600	1,500	2,600	35	6.0	3	474	3,450	4,173	30,400	1,091	7,940	7,385	53,800	
0400-001	400	94	78	93,300	10.0	17,600	1,500	2,600	35	6.0	3	474	4,420	4,173	38,900	1,091	10,200	7,385	68,900	
0500-001	500	116	88	106,000	10.0	17,600	1,500	2,600	35	6.0	3	474	5,020	4,173	44,200	1,091	11,600	7,385	78,300	
0600-001	600	141	106	119,000	10.0	17,600	1,500	2,600	35	6.0	3	474	5,640	4,173	49,700	1,091	13,000	7,385	87,900	
0800-001	800	169	126	143,000	10.0	17,600	1,500	2,600	35	6.0	3	474	6,780	4,173	59,700	1,091	15,600	7,385	106,000	
1000-001	1,000	197	145	171,000	10.0	17,600	1,500	2,600	35	6.0	3	474	8,110	4,173	71,400	1,091	18,700	7,385	126,000	
028 〔角型シクナ・鋼板製〕																				
処理能力																				
0050-001	50 m ³ /h	20	19	21,500	10.0	17,600	1,500	2,600	35	6.0	3	474	1,020	4,173	8,970	1,091	2,350	7,385	15,900	
0100-001	100	28	26	31,900	10.0	17,600	1,500	2,600	35	6.0	3	474	1,510	4,173	13,300	1,091	3,480	7,385	23,600	
0150-001	150	35	35	39,300	10.0	17,600	1,500	2,600	35	6.0	3	474	1,860	4,173	16,400	1,091	4,290	7,385	29,000	
0200-001	200	50	45	49,600	10.0	17,600	1,500	2,600	35	6.0	3	474	2,350	4,173	20,700	1,091	5,410	7,385	36,600	
0250-001	250	55	55	62,700	10.0	17,600	1,500	2,600	35	6.0	3	474	2,970	4,173	26,200	1,091	6,840	7,385	46,300	

46 公害対策設備

分類コード	規 格			(1)	(2)	標準使用			(6)	(7)	残 存 率 (%)	運転1時間当たり		供用1日当たり		換算値				摘 要
	諸 元	機関出力 (kW)	機械 質量 (t)	基礎価格 (千円)	標準使 用 年数 (年)	(3) 運転 時間 (時間)	(4) 運転 日数 (日)	(5) 供用 日数 (日)	整備修 理費率 (%)	年間管 理費率 (%)		(8) 損料率 (×10-7)	(9) 損 料 (円)	(10) 損料率 (×10-7)	(11) 損 料 (円)	運転1時間当たり		供用1日当たり		
																(12) 損料率 (×10-7)	(13) 損 料 (円)	(14) 損料率 (×10-7)	(15) 損 料 (円)	
																				建屋、薬品供給装置、攪拌槽、原水ポンプ、 排泥ポンプ(輸送距離10m)を含み、原水 送水用トイ、原水槽、排泥配管、脱水機、 中和装置等は含まない。
4602 濁水処理プラント（ダムサイト用）																				
018 〔丸型シクナ・鋼板製〕																				
処理能力																				
0100-001	100 m ³ /h	38	35	43,500	11.9	59,300	2,600	3,100	20	6.0	3	116	505	3,868	16,800	318	1,380	6,077	26,400	
0150-001	150	45	40	51,400	11.9	59,300	2,600	3,100	20	6.0	3	116	596	3,868	19,900	318	1,630	6,077	31,200	
0200-001	200	60	51	60,300	11.9	59,300	2,600	3,100	20	6.0	3	116	699	3,868	23,300	318	1,920	6,077	36,600	
0250-001	250	66	60	66,100	11.9	59,300	2,600	3,100	20	6.0	3	116	767	3,868	25,600	318	2,100	6,077	40,200	
0300-001	300	86	66	76,000	11.9	59,300	2,600	3,100	20	6.0	3	116	882	3,868	29,400	318	2,420	6,077	46,200	
0400-001	400	94	78	97,500	11.9	59,300	2,600	3,100	20	6.0	3	116	1,130	3,868	37,700	318	3,100	6,077	59,300	
0500-001	500	116	88	112,000	11.9	59,300	2,600	3,100	20	6.0	3	116	1,300	3,868	43,300	318	3,560	6,077	68,100	
0600-001	600	141	106	126,000	11.9	59,300	2,600	3,100	20	6.0	3	116	1,460	3,868	48,700	318	4,010	6,077	76,600	
0800-001	800	169	126	153,000	11.9	59,300	2,600	3,100	20	6.0	3	116	1,770	3,868	59,200	318	4,870	6,077	93,000	
1000-001	1,000	197	145	182,000	11.9	59,300	2,600	3,100	20	6.0	3	116	2,110	3,868	70,400	318	5,790	6,077	111,000	
028 〔角型シクナ・鋼板製〕																				
処理能力																				
0050-001	50 m ³ /h	20	19	25,200	11.9	59,300	2,600	3,100	20	6.0	3	116	292	3,868	9,750	318	801	6,077		15,300
0100-001	100	28	26	36,600	11.9	59,300	2,600	3,100	20	6.0	3	116	425	3,868	14,200	318	1,160	6,077		22,200
0150-001	150	35	35	45,600	11.9	59,300	2,600	3,100	20	6.0	3	116	529	3,868	17,600	318	1,450	6,077		27,700
0200-001	200	50	45	57,600	11.9	59,300	2,600	3,100	20	6.0	3	116	668	3,868	22,300	318	1,830	6,077		35,000
0250-001	250	55	55	72,900	11.9	59,300	2,600	3,100	20	6.0	3	116	846	3,868	28,200	318	2,320	6,077	44,300	
																			建屋、貯留槽、圧入ポンプ、洗浄水ポンプ、 コンプレッサ、油圧ユニットのほか、高脚架 台を含む。損料は、半自動型の場合とする。 自動開枠型の場合の損料は、20%増しと する。	
4603 加圧脱水機（骨材プラント用）																				
018 〔フィルタプレス式〕																				
ろ過面積																				
0100-001	100 m ²	31	33	37,000	10.0	17,600	1,500	2,600	40	6.0	3	503	1,860	4,173	15,400	1,119	4,140	7,577		28,000
0150-001	150	34	40	42,300	10.0	17,600	1,500	2,600	40	6.0	3	503	2,130	4,173	17,700	1,119	4,730	7,577		32,100
0200-001	200	37	48	47,000	10.0	17,600	1,500	2,600	40	6.0	3	503	2,360	4,173	19,600	1,119	5,260	7,577		35,600
0250-001	250	42	59	61,200	10.0	17,600	1,500	2,600	40	6.0	3	503	3,080	4,173	25,500	1,119	6,850	7,577		46,400
0300-001	300	46	65	66,200	10.0	17,600	1,500	2,600	40	6.0	3	503	3,330	4,173	27,600	1,119	7,410	7,577		50,200
0400-001	400	54	70	72,500	10.0	17,600	1,500	2,600	40	6.0	3	503	3,650	4,173	30,300	1,119	8,110	7,577		54,900
0600-001	600	62	96	106,000	10.0	17,600	1,500	2,600	40	6.0	3	503	5,330	4,173	44,200	1,119	11,900	7,577		80,300
0900-001	900	74	134	156,000	10.0	17,600	1,500	2,600	40	6.0	3	503	7,850	4,173	65,100	1,119	17,500	7,577		118,000
028 〔ベルト式〕																				
0001-001	各種	—	—	—	10.0	17,600	1,500	2,600	40	6.0	3	503	—	4,173	—	1,119	—	7,577		—

46 公害対策設備

分類コード	規 格			(1)	(2)	標準使用			(6)	(7)	残 存 率 (%)	運転1時間当たり		供用1日当たり		換算値				摘 要
	諸 元	機関出力 (kW)	機械 質量 (t)	基礎価格 (千円)	標準使用 年数 (年)	(3) 運転 時間 (時間)	(4) 運転 日数 (日)	(5) 供用 日数 (日)	整備修 理費率 (%)	年間管 理費率 (%)		(8) 損料率 (×10-7)	(9) 損 料 (円)	(10) 損料率 (×10-7)	(11) 損 料 (円)	運転1時間当たり		供用1日当たり		
																(12) 損料率 (×10-7)	(13) 損 料 (円)	(14) 損料率 (×10-7)	(15) 損 料 (円)	
4604 加圧脱水機（ダムサイト用） 018 〔フィルタプレス式〕																				建屋、貯留槽、圧入ポンプ、洗浄水ポンプ、コンプレッサ、油圧ユニットのほか、高脚架台を含む。損料は、半自動型の場合とする。自動開枠型の場合の損料は20%増しとする。
ろ過面積																				
0050-001	50 m ²	28	20	30,900	11.9	59,300	2,600	3,100	25	6.0	3	124	383	3,868	12,000	326	1,010	6,239	19,300	
0100-001	100	31	33	38,700	11.9	59,300	2,600	3,100	25	6.0	3	124	480	3,868	15,000	326	1,260	6,239	24,100	
0150-001	150	34	40	44,300	11.9	59,300	2,600	3,100	25	6.0	3	124	549	3,868	17,100	326	1,440	6,239	27,600	
0200-001	200	37	48	49,300	11.9	59,300	2,600	3,100	25	6.0	3	124	611	3,868	19,100	326	1,610	6,239	30,800	
0250-001	250	42	59	64,100	11.9	59,300	2,600	3,100	25	6.0	3	124	795	3,868	24,800	326	2,090	6,239	40,000	
0300-001	300	46	65	69,200	11.9	59,300	2,600	3,100	25	6.0	3	124	858	3,868	26,800	326	2,260	6,239	43,200	
028 〔ベルト式〕																				中和反応槽、炭酸ガス貯槽、原水槽、原水ポンプ、制御装置を含む。
0001-001	各種	－	－	－	11.9	59,300	2,600	3,100	25	6.0	3	124	－	3,868	－	326	－	6,239	－	
4605 中和処理設備（骨材プラント用） 018 〔炭酸ガス式〕																				
処理能力																				
0025-001	25 m ³ /h	8	2.4	8,330	10.0	17,600	1,500	2,600	45	6.0	3	531	442	4,173	3,480	1,148	956	7,769	6,470	
0050-001	50	11	3.1	10,400	10.0	17,600	1,500	2,600	45	6.0	3	531	552	4,173	4,340	1,148	1,190	7,769	8,080	
0100-001	100	19	4.9	13,200	10.0	17,600	1,500	2,600	45	6.0	3	531	701	4,173	5,510	1,148	1,520	7,769	10,300	
0150-001	150	32	6.5	17,100	10.0	17,600	1,500	2,600	45	6.0	3	531	908	4,173	7,140	1,148	1,960	7,769	13,300	
0200-001	200	35	8.7	19,300	10.0	17,600	1,500	2,600	45	6.0	3	531	1,020	4,173	8,050	1,148	2,220	7,769	15,000	
4606 中和処理設備（ダムサイト用） 018 〔炭酸ガス式〕																				中和反応槽、炭酸ガス貯槽、原水槽、原水ポンプ、制御装置を含む。
処理能力																				
0025-001	25 m ³ /h	8	2.4	8,100	11.9	59,300	2,600	3,100	25	6.0	3	124	100	3,868	3,130	326	264	6,239	5,050	
0050-001	50	11	3.1	10,200	11.9	59,300	2,600	3,100	25	6.0	3	124	126	3,868	3,950	326	333	6,239	6,360	
0100-001	100	19	4.9	12,800	11.9	59,300	2,600	3,100	25	6.0	3	124	159	3,868	4,950	326	417	6,239	7,990	
0150-001	150	32	6.5	16,600	11.9	59,300	2,600	3,100	25	6.0	3	124	206	3,868	6,420	326	541	6,239	10,400	
0200-001	200	35	8.7	18,800	11.9	59,300	2,600	3,100	25	6.0	3	124	233	3,868	7,270	326	613	6,239	11,700	
0300-001	300	47	13.0	25,800	11.9	59,300	2,600	3,100	25	6.0	3	124	320	3,868	9,980	326	841	6,239	16,100	
0400-001	400	63	17.0	33,000	11.9	59,300	2,600	3,100	25	6.0	3	124	409	3,868	12,800	326	1,080	6,239	20,600	

47 その他ダム施工機械等

分類コード	規 格			(1)	(2)	標準使用			(6)	(7)	残 存 率 (%)	運転1時間当たり		供用1日当たり		換算値				摘 要
	諸 元	機関出力 (kW)	機械 質量 (t)	基礎価格 (千円)	標準使 用 年数 (年)	(3)	(4)	(5)	整備修 理費率 (%)	年間管 理費率 (%)		(8)	(9)	(10)	(11)	運転1時間当たり		供用1日当たり		
						運 転 時 間 (時間)	運 転 日 数 (日)	供 用 日 数 (日)				損 料 率 (×10-7)	損 料 (円)	損料率 (×10-7)	損 料 (円)	(12) 損料率 (×10-7)	(13) 損 料 (円)	(14) 損料率 (×10-7)	(15) 損 料 (円)	
47 その他ダム施工機械等																				棒状バイブレータ3本装着(径130又は150) 棒状バイブレータ4本装着(径130又は150)。 5本(3本)装着の場合は基礎価格に 684千円加(減)算する。 棒状バイブレータ4本装着 (径150)
4701 コンクリート締固機																				
011 〔電動振動式〕																				
0070-001	平積み0.2m ³ 級ハック付	24	4.2	12,400	5.6	4,400	630	1,100	50	7.0	3	2,239	2,780	7,973	9,890	4,232	5,250	16,927	21,000	
0090-001	平積み0.3m ³ 級ハック付	45	7.8	15,900	5.6	4,400	630	1,100	50	7.0	3	2,239	3,560	7,973	12,700	4,232	6,730	16,927	26,900	
021 〔油圧振動式〕																				
0100-001	平積み0.3m ³ 級ハック付	40	7.3	19,400	5.6	3,600	490	1,100	45	7.0	3	2,597	5,040	7,973	15,500	5,033	9,760	16,473	32,000	
031 〔振動ローラ (RCD用) 〕																				
0100-001	質量 11 t	99	10.6	34,800	5.6	4,000	450	1,100	45	7.0	3	2,338	8,140	7,973	27,700	4,530	15,800	16,473	57,300	
041 〔章動ローラ (ウレタンロール) 排出ガス対策型 (第3次基準値) 〕																				
0100-001	質量 7t	55	7.4	17,600	5.6	3,100	450	1,100	45	7.0	3	3,016	5,310	7,973	14,000	5,845	10,300	16,473	29,000	
051 〔手動型バイブレータ〕																				整備修理費率には、ウレタンロールの取替え費用を含む。
0130-001	振動部外径 φ130 200(V)	1.85	0.05	384	5.6	—	490	1,100	50	6.0	3	(日) 20,102	(日) 772	7,464	287	(日) 36,857	(日) 1,420	16,418	630	
052 〔高周波インバータ (手動型バイブレータ用) 〕																				
0130-001	定格容量 (入力) 13.0kVA 200 (V) 定格容量 (出力) 10.0kVA 200 (V)	10	0.18	1,440	5.6	—	490	1,100	50	6.0	3	(日) 20,102	(日) 2,890	7,464	1,070	(日) 36,857	(日) 5,310	16,418	2,360	
4702 コンクリート表面掃除機																				連続使用可能なバイブレータ(φ130)台数は3台。 ワイヤブラシ、キャブタイヤケーブル等を含む。 ブラシ交換費として基礎価格の3%を別途計上する。
017 〔手動型〕																				
0750-001	電動式 30 cm	0.75	0.03	200	3.9	—	—	1,000	—	6.0	3	—	—	12,040	241	—	—	12,040	241	
022 〔自走型・ブラシ式〕																				
0001-001	各種	—	—	—	6.6	3,200	560	1,400	25	7.0	3	2,297	—	6,764	—	5,256	—	12,014	—	
032 〔自走型・高圧水式〕																				
0001-001	各種	—	—	—	3.8	4,200	440	1,000	25	7.0	3	1,750	—	7,510	—	3,538	—	14,860	—	

47 その他ダム施工機械等

分類コード	規 格			(1)	(2)	標準使用			(6)	(7)	残 存 率 (%)	運転1時間当たり		供用1日当たり		換算値				摘 要
	諸 元	機関出力 (kW)	機械 質量 (t)	基礎価格 (千円)	標準使 用 年数 (年)	(3)	(4)	(5)	整備修 理費率 (%)	年間管 理費率 (%)		(8)	(9)	(10)	(11)	運転1時間当たり		供用1日当たり		
						運 転 時 間 (時間)	運 転 日 数 (日)	供 用 日 数 (日)				損 料 率 (×10-7)	損 料 (円)	損料率 (×10-7)	損 料 (円)	(12) 損料率 (×10-7)	(13) 損 料 (円)	(14) 損料率 (×10-7)	(15) 損 料 (円)	
4703 スライム回収機																				セメントミルク圧送配管及び制御ケーブルとして、 269 千円/100mを 基礎価格に加算する。
012 〔自走式〕																				
0001-001	18m ³ /分	(走行)151 (作業) 29	6	17,900	6.4	8,200	910	1,200	30	7.0	3	957	1,710	7,775	13,900	2,095	3,750	14,317	25,600	
028 〔定置型〕																				
0001-001	各種	—	—	—	6.4	7,700	920	1,200	20	7.0	3	890	—	7,775	—	2,101	—	13,483	—	
4704 引出しゲート																				
017- 0001-001	各種	—	—	—	3.8	—	570	1,000	—	6.0	3	(日) 8,509	—	7,130	—	(日) 21,018	—	11,980	—	
4705 貯蔵ビン																				
017- 0001-001	各種	—	—	—	3.9	—	—	1,300	—	6.0	3	—	—	9,262	—	—	—	9,262	—	
4706 グリズリ																				
017- 0001-001	各種	—	—	—	3.8	—	—	1,200	40	6.0	3	—	—	13,317	—	—	—	13,317	—	
4707 スクリーンタワー																				
017- 0001-001	各種	—	—	—	3.8	—	—	1,200	—	6.0	3	—	—	9,983	—	—	—	9,983	—	
4708 架台																				
017- 0001-001	各種	—	—	—	4.5	—	—	1,500	—	6.0	3	—	—	8,267	—	—	—	8,267	—	
4709 操作盤																				
017- 0001-001	各種	—	—	—	4.2	—	—	1,500	—	6.0	3	—	—	8,147	—	—	—	8,147	—	
4710 脚及びロックラダー																				
017- 0001-001	各種	—	—	—	3.8	—	—	1,100	—	6.0	3	—	—	10,891	—	—	—	10,891	—	
4711 グラウト中央プラント																				
供給量																				
017- 0100-001	100 L/min	56	8.8	28,100	9.4	—	1,100	1,700	30	6.0	3	(日) 7,136	(日) 20,100	6,171	17,300	(日) 16,673	(日) 46,900	10,788	30,300	
0150-001	150	60	9.5	28,900	9.4	—	1,100	1,700	30	6.0	3	(日) 7,136	(日) 20,600	6,171	17,800	(日) 16,673	(日) 48,200	10,788	31,200	
4712 グラウトデータレコーダ																				
017- 0001-001	グラウトデータレコーダ	—	—	—	9.4	—	1,100	1,700	20	6.0	3	(日) 6,227	—	6,171	—	(日) 15,764	—	10,200	—	
4713 グラウトデータ処理装置																				
017- 0001-001	各種	—	—	—	5.8	—	—	1,100	—	6.0	3	—	—	11,982	—	—	—	11,982	—	
4714 振動目地切機																				
振動力																				
017- 0001-001	255 kN (26t) 〔平積み0.4m ³ 級〕	63	13	18,900	7.7	2,700	810	2,100	30	7.0	3	2,907	5,490	4,876	9,220	6,700	12,700	8,614	16,300	750mm用